



LED STREET LIGHTS



✓ Applications

Street Lighting
Parkways
Residential / Commercial Building
Factory / Building Premises
Highways

» Features and Benefits

1. White Light Output from LED
2. CRI >80
3. Life 50000 Hrs.
4. Ingress Protection IP65
5. No water stagnation
6. Weather proof surface coating

LED STREET LIGHTS


General Specifications

Product Description	LED STREET LIGHT
Color Rendering Index (Ra)	>80
Driver Input Voltage	130VAC - 270VAC
Housing	DIE CAST ALUMINUM HEAT SINK HOUSING
IP Rating	IP 65 / IP 66
LED Efficacy	> 120 Lm/W
LED Make	NICHIA / OSRAM
Life Span	Rated 50,000 Hrs
Power factor	> 0.9
Rated Input Frequency	50Hz
Storage Temperature	-10°C to 65°C
System Efficiency	> 85%
Working Temperature	-10°C to 50°C

*More Technical details available on request.



Product Description	Product Code	Asthetic	Power Rating	CCT range	Dimensions	Beam Angle
LED STREET LIGHT 15W CW w/o Lens	BLSLNZ015CCW1	Toughen Glass	15W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 15W CW with Lens	BLSLNZ015CCW2	Toughen Glass	15W	5600K-6500K	400 x 175 x75mm	120° X 60°
LED STREET LIGHT 24W CW w/o Lens	BLSLNZ024CCW1	Toughen Glass	24W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 24W CW with Lens	BLSLNZ024CCW2	Toughen Glass	24W	5600K-6500K	400 x 175 x75mm	120° X 60°
LED STREET LIGHT 30W CW w/o Lens	BLSLNZ030CCW1	Toughen Glass	30W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 30W CW with Lens	BLSLNZ030CCW2	Toughen Glass	30W	5600K-6500K	400 x 175 x75mm	120° X 60°
LED STREET LIGHT 40W CW w/o Lens	BLSLNZ036CCW1	Toughen Glass	40W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 40W CW with Lens	BLSLNZ036CCW2	Toughen Glass	40W	5600K-6500K	430 x 230 x85mm	120° X 60°
LED STREET LIGHT 50W CW w/o Lens	BLSLNZ048CCW1	Toughen Glass	50W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 50W CW with Lens	BLSLNZ048CCW2	Toughen Glass	50W	5600K-6500K	430 x 230 x85mm	120° X 60°
LED STREET LIGHT 60W CW w/o Lens	BLSLNZ060CCW1	Toughen Glass	60W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 60W CW with Lens	BLSLNZ060CCW2	Toughen Glass	60W	5600K-6500K	430 x 230 x85mm	120° X 60°
LED STREET LIGHT 70W CW w/o Lens	BLSLNZ070CCW1	Toughen Glass	70W	5600K-6500K	585x280x105mm	120°
LED STREET LIGHT 70W CW with Lens	BLSLNZ070CCW2	Toughen Glass	70W	5600K-6500K	585x280x105mm	120° X 60°
LED STREET LIGHT 90W CW w/o Lens	BLSLNZ090CCW1	Toughen Glass	90W	5600K-6500K	585x280x105mm	120°
LED STREET LIGHT 90W CW with Lens	BLSLNZ090CCW2	Toughen Glass	90W	5600K-6500K	585x280x105mm	120° X 60°
LED STREET LIGHT 110W CW w/o Lens	BLSLNZ110CCW1	Toughen Glass	110W	5600K-6500K	650x310x105mm	120°
LED STREET LIGHT 110W CW with Lens	BLSLNZ110CCW2	Toughen Glass	110W	5600K-6500K	650x310x105mm	120° X 60°



*AVAILABLE UPTO 1000 W

Head Office:

BIRLA LED

VINDHYA TELELINKS LIMITED

Sharda Terraces, 9th & 10th Floor, Plot No.:65,
Sector-11, CBD Belapur, Navi Mumbai-400 614,
Maharashtra, India

Tel : +91 22 41268855/ 27560463/ 64,

Fax : +91 22 41268899

Email : info@vtlrewa.com

www.vtlrewa.com/leddivision.html

Branch Offices:

New Delhi : +91 11 45538800

Bangalore : +91 80 23612484/ 9981

Chennai : +91 44 23746623/ 24

Hyderabad : +91 40 23550183/ 608218

Kolkata : +91 33 22805043/ 44

Goa : +91 832 2782613/ 2829

Bhopal : +91 755 2551183/ 4220313

Vadodara : +91 265 2791794/ 5642