



## LED DOWNLIGHT ROUND

### ✓ Applications

Offices  
Showrooms  
Hospitals  
Corridors  
Residential

### » Features and Benefits

1. High Power LEDs generating white light
2. CRI >80
3. Long Life > 50000 Hrs.
4. Soothing white light output
5. Available with dimming

# LED DOWNLIGHT ROUND


General Specifications	
Product Description	LED DOWNLIGHT ROUND
Color Rendering Index (Ra)	>80
Driver Input Voltage	130VAC - 270VAC**
Housing	DIE CAST ALUMINUM HEAT SINK WITH MILKY WHITE ACRYLIC DIFFUSER
LED Efficacy	> 120 lm/W
LED Make	OSRAM
Life Span	Rated 50,000 Hrs
Power factor	>0.9
Rated Input Frequency	50Hz
Storage Temperature	-10°C to 65°C
System Efficiency	>80%
Application	Indoor
Working Temperature	-10°C to 50°C

\*\* with external driver

\*More Technical details available on request.



Product Description	Product Code	Aesthetic	Power Rating	CCT range	Dimensions	Beam Angle
LED DOWNLIGHT 9W CW	BLDLOZ015ACW1	White Diffused	9W	5600K-6500K	Dia 150mm x 45mm	120°
LED DOWNLIGHT 9W WW	BLDLOZ015AWW1	White Diffused	9W	2750K - 3250K	Dia 150mm x 45mm	120°
LED DOWNLIGHT 15W CW	BLDLOZ015ACW1	White Diffused	15W	5600K-6500K	Dia 180mm x 78mm	120°
LED DOWNLIGHT 15W WW	BLDLOZ015AWW1	White Diffused	15W	2750K - 3250K	Dia 180mm x 78mm	120°



## Head Office:

**BIRLA LED**

**VINDHYA TELELINKS LIMITED**

Sharda Terraces, 9th & 10th Floor, Plot No.:65,  
Sector-11, CBD Belapur, Navi Mumbai-400 614,  
Maharashtra, India

Tel : +91 22 41268855/ 27560463/ 64,

Fax : +91 22 41268899

Email : info@vtlrewa.com

www.vtlrewa.com/leddivision.html

## Branch Offices:

New Delhi : +91 11 45538800

Bangalore : +91 80 23612484/ 9981

Chennai : +91 44 23746623/ 24

Hyderabad : +91 40 23550183/ 608218

Kolkata : +91 33 22805043/ 44

Goa : +91 832 2782613/ 2829

Bhopal : +91 755 2551183/ 4220313

Vadodara : +91 265 2791794/ 5642