



LED STREET LIGHTS

✓ Applications

Street Lighting
Parkways
Residential / Commercial Building
Factory / Building Premises
Highways

» Features and Benefits

1. White Light Output from LED
2. CRI >80
3. Life 50000 Hrs.
4. Ingress Protection IP65
5. No water stagnation
6. Weather proof surface coating

BIRLA LED

 **Vindhya Telalinks Ltd.**


LED STREET LIGHTS



General Specifications	
Product Description	LED STREET LIGHT IP65
Color Rendering Index (Ra)	>80
Driver Input Voltage	130VAC - 270VAC
Housing	DIE CAST ALUMINUM HEAT SINK HOUSING
IP Rating	IP 65 / IP 66
LED Efficacy	>120 Lm/W
LED Make	NICHIA/CREE/OSRAM
Life Span	Rated 50,000 Hrs
Power factor	> 0.9
Rated Input Frequency	50Hz
Storage Temperature	-10°C to 65°C
System Efficiency	> 85%
Working Temperature	-10°C to 50°C

*More Technical details available on request.

Product Description	Product Code	Aesthetic	Power Rating	CCT range	Dimensions	Beam Angle
LED STREET LIGHT 20W CW	BLSLNZ020CCW1	Clear Transparent	20W	5600K-6500K	400 x 175 x75mm	120° X 70°
LED STREET LIGHT 20W CW TYPE-II	BLSLNZ020CCW2	Clear Transparent	20W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 24W CW	BLSLNZ024CCW1	Clear Transparent	24W	5600K-6500K	400 x 175 x75mm	120° X 70°
LED STREET LIGHT 24W CW TYPE-II	BLSLNZ024CCW2	Clear Transparent	24W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 30W CW	BLSLNZ030CCW1	Clear Transparent	30W	5600K-6500K	400 x 175 x75mm	120° X 70°
LED STREET LIGHT 30W CW TYPE-II	BLSLNZ030CCW2	Clear Transparent	30W	5600K-6500K	400 x 175 x75mm	120°
LED STREET LIGHT 36W CW	BLSLNZ036CCW1	Clear Transparent	36W	5600K-6500K	430 x 230 x85mm	120° X 70°
LED STREET LIGHT 36W CW TYPE-II	BLSLNZ036CCW2	Clear Transparent	36W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 48W CW	BLSLNZ048CCW1	Clear Transparent	48W	5600K-6500K	430 x 230 x85mm	120° X 70°
LED STREET LIGHT 48W CW TYPE-II	BLSLNZ048CCW2	Clear Transparent	48W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 60W CW	BLSLNZ060CCW1	Clear Transparent	60W	5600K-6500K	430 x 230 x85mm	120° X 70°
LED STREET LIGHT 60W CW TYPE-II	BLSLNZ060CCW2	Clear Transparent	60W	5600K-6500K	430 x 230 x85mm	120°
LED STREET LIGHT 70W CW	BLSLNZ070CCW1	Clear Transparent	70W	5600K-6500K	585x280x105mm	120° X 70°
LED STREET LIGHT 70W CW TYPE-II	BLSLNZ070CCW2	Clear Transparent	70W	5600K-6500K	585x280x105mm	120°
LED STREET LIGHT 90W CW	BLSLNZ090CCW1	Clear Transparent	90W	5600K-6500K	585x280x105mm	120° X 70°
LED STREET LIGHT 90W CW TYPE-II	BLSLNZ090CCW2	Clear Transparent	90W	5600K-6500K	585x280x105mm	120°
LED STREET LIGHT 110W CW	BLSLNZ110CCW1	Clear Transparent	110W	5600K-6500K	650x310x105mm	120° X 70°
LED STREET LIGHT 110W CW TYPE-II	BLSLNZ110CCW2	Clear Transparent	110W	5600K-6500K	650x310x105mm	120°



Head Office:

BIRLA LED

VINDHYA TELELINKS LIMITED

Sharda Terraces, 9th & 10th Floor, Plot No.:65,
Sector-11, CBD Belapur, Navi Mumbai-400 614,
Maharashtra, India

Tel : +91 22 41268855/ 27560463/ 64,

Fax : +91 22 41268899

Email : info@vtlrewa.com

www.vtlrewa.com/leddivision.html

Branch Offices:

New Delhi : +91 11 45538800

Bangalore : +91 80 23612484/ 9981

Chennai : +91 44 23746623/ 24

Hyderabad : +91 40 23550183/ 608218

Kolkata : +91 33 22805043/ 44

Goa : +91 832 2782613/ 2829

Bhopal : +91 755 2551183/ 4220313

Vadodara : +91 265 2791794/ 5642