



LED FLOOD LIGHTS



✓ Applications

Building Facade
Wall Highlighting
Outdoor Lighting

» Features and Benefits

1. High Power LEDs generating white light
2. CRI >80
3. Long Life 50000 Hrs.
4. Ingress Protection IP65

LED FLOOD LIGHT




General Specifications

Product Description	LED FLOOD LIGHT
Color Rendering Index (Ra)	>80
Driver Input Voltage	130VAC - 270VAC
Housing	DIE CAST ALUMINUM HEAT SINK HOUSING
IP Rating	IP65
LED Efficacy	>120 lm/W
LED Make	NICHIA / OSRAM
Life Span	Rated 50,000 Hrs
Power factor	>0.9
Rated Input Frequency	50Hz
Storage Temperature	-10°C to 65°C
System Efficiency	>80%
Application	Outdoor
Working Temperature	-10°C to 50°C

*More Technical details available on request.

Product Description	Product Code	Aesthetic	Power Rating	CCT range	Dimensions	Beam Angle
LED FLOOD LIGHT 36W CW 120D	BLFDNZ030CCW1	Clear Transparent	36W	5600K-6500K	260 x 105 x 120mm	120°
LED FLOOD LIGHT 36W CW 60D	BLFDNZ030CCW2	Clear Transparent	36W	5600K-6500K	260 x 105 x 120mm	60°
LED FLOOD LIGHT 48W CW 120D	BLFDNZ048CCW1	Clear Transparent	48W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 48W CW 60D	BLFDNZ048CCW2	Clear Transparent	48W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 60W CW 120D	BLFDNZ060CCW1	Clear Transparent	60W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 60W CW 60D	BLFDNZ060CCW2	Clear Transparent	60W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 60W CW 30D	BLFDNZ060CCW3	Clear Transparent	60W	5600K-6500K	279 x 204 x 196mm	30°
LED FLOOD LIGHT 70W CW 120D	BLFDNZ070CCW1	Clear Transparent	70W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 70W CW 60D	BLFDNZ070CCW2	Clear Transparent	70W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 70W CW 30D	BLFDNZ070CCW3	Clear Transparent	70W	5600K-6500K	279 x 204 x 196mm	30°
LED FLOOD LIGHT 90W CW 120D	BLFDNZ090CCW1	Clear Transparent	90W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 90W CW 60D	BLFDNZ090CCW2	Clear Transparent	90W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 90W CW 30D	BLFDNZ090CCW3	Clear Transparent	90W	5600K-6500K	279 x 204 x 196mm	30°
LED FLOOD LIGHT 100W CW 120D	BLFDNZ100CCW1	Clear Transparent	100W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 100W CW 60D	BLFDNZ100CCW2	Clear Transparent	100W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 100W CW 30D	BLFDNZ100CCW3	Clear Transparent	100W	5600K-6500K	279 x 204 x 196mm	30°
LED FLOOD LIGHT 120W CW 120D	BLFDNZ120CCW1	Clear Transparent	120W	5600K-6500K	279 x 204 x 196mm	120°
LED FLOOD LIGHT 120W CW 60D	BLFDNZ120CCW2	Clear Transparent	120W	5600K-6500K	279 x 204 x 196mm	60°
LED FLOOD LIGHT 120W CW 30D	BLFDNZ120CCW3	Clear Transparent	120W	5600K-6500K	279 x 204 x 196mm	30°

* AVAILABLE UPTO 1000 W



Head Office:

BIRLA LED

VINDHYA TELELINKS LIMITED

Sharda Terraces, 9th & 10th Floor, Plot No.:65,
Sector-11, CBD Belapur, Navi Mumbai-400 614,
Maharashtra, India

Tel : +91 22 41268855/ 27560463/ 64,

Fax : +91 22 41268899

Email : info@vtlrewa.com

www.vtlrewa.com/leddivision.html

Branch Offices:

New Delhi : +91 11 45538800

Bangalore : +91 80 23612484/ 9981

Chennai : +91 44 23746623/ 24

Hyderabad : +91 40 23550183/ 608218

Kolkata : +91 33 22805043/ 44

Goa : +91 832 2782613/ 2829

Bhopal : +91 755 2551183/ 4220313

Vadodara : +91 265 2791794/ 5642