



LED HIGHBAY LIGHTS



✓ Applications

Warehouse
Factories
Open shades
Industrial premises

» Features and Benefits

1. White Light Output from LED
2. CRI >80
3. Long Life 50000 Hrs.
4. Ingress Protection IP54

LED HIGHBAY LAMP

General Specifications	
Product Description	LED HIGHBAY LAMP
Color Rendering Index (Ra)	>80
Driver Input Voltage	130VAC - 270VAC
Housing	EXTRUDED ALUMINUM HEAT SINK WITH AL REFLECTOR
IP Rating	IP54 / IP65
LED Efficacy	> 120 lm/W
LED Make	CREE / CITIZEN
Life Span	Rated 50,000 Hrs
Power factor	>0.95
Rated Input Frequency	50Hz
Storage Temperature	-10°C to 65°C
System Efficiency	>85%
Application	Indoor
Working Temperature	-10°C to 50°C



*More Technical details available on request.

Product Description	Product Code	Aesthetic	Power Rating	CCT range	Dimensions	Beam Angle
LED HIGHBAY 40W CW	BLHBCZ040CCW1	Clear Glass Lens	40W	5600K-6500K	246X 240 X500mm	90° / 60°
LED HIGHBAY 50W CW	BLHBCZ050CCW1	Clear Glass Lens	50W	5600K-6500K	246X 240 X500mm	120° / 90°
LED HIGHBAY 80W CW	BLHBCZ080CCW1	Clear Glass Lens	80W	5600K-6500K	246X 240 X500mm	120° / 90°
LED HIGHBAY 100W CW	BLHBCZ100CCW1	Clear Glass Lens	100W	5600K-6500K	246X 240 X500mm	120° / 90°
LED HIGHBAY 120W CW	BLHBCZ120CCW1	Clear Glass Lens	120W	5600K-6500K	246X 240 X500mm	90°
LED HIGHBAY 150W CW	BLHBCZ150CCW1	Clear Glass Lens	150W	5600K-6500K	495X 475X 500mm	90°

*AVAILABLE UPTO 1000 W



Head Office:

BIRLA LED

VINDHYA TELELINKS LIMITED

Sharda Terraces, 9th & 10th Floor, Plot No.:65,
Sector-11, CBD Belapur, Navi Mumbai-400 614,
Maharashtra, India

Tel : +91 22 41268855/ 27560463/ 64,

Fax : +91 22 41268899

Email : info@vtlrewa.com

www.vtlrewa.com/leddivision.html

Branch Offices:

New Delhi : +91 11 45538800

Bangalore : +91 80 23612484/ 9981

Chennai : +91 44 23746623/ 24

Hyderabad : +91 40 23550183/ 608218

Kolkata : +91 33 22805043/ 44

Goa : +91 832 2782613/ 2829

Bhopal : +91 755 2551183/ 4220313

Vadodara : +91 265 2791794/ 5642